

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**


The **ASI 2SC2652** is Designed for High Linearity Class A, AB HF Power Amplifier Applications up to 30 MHz.

**FEATURES:**

- $P_E = 15$  dB Typical at 200 W/28 MHz
- $IMD_3 = -30$  dBc Max. at 220 W(PEP)
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

$I_C$	20 A
$V_{CES}$	85 V
$V_{CEO}$	55 V
$V_{EBO}$	4.0 V
$P_{DISS}$	300 W @ $T_C = 25$ °C
$T_J$	-65 °C to +200 °C
$T_{STG}$	-65 °C to +175 °C
$\theta_{JC}$	0.7 °C/W

**PACKAGE STYLE .500 4L FLG**


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B		.125 / 3.18
C	.245 / 6.22	.255 / 6.48
D	.720 / 18.28	.730 / 18.54
E		.125 / 3.18
F	.970 / 24.64	.980 / 24.89
G	.495 / 12.57	.505 / 12.83
H	.003 / 0.08	.007 / 0.18
I	.090 / 2.29	.110 / 2.79
J	.150 / 3.81	.175 / 4.45
K		.280 / 7.11
L	.980 / 24.89	1.050 / 26.67

**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
$BV_{CES}$	$I_C = 100$ mA	85			V
$BV_{CEO}$	$I_C = 100$ mA	55			V
$BV_{EBO}$	$I_E = 1.0$ mA	4.0			V
$I_{CES}$	$V_{CE} = 55$ V			10	mA
$h_{FE}$	$V_{CE} = 5.0$ V $I_C = 10$ A	10		150	---
$C_{ob}$	$V_{CB} = 50$ V $f = 1.0$ MHz		300		pF
$G_P$	$V_{CC} = 50$ V $I_{CQ} = 100$ mA $P_{OUT} = 200$ W(PEP)	13.0	15.2		dB
IMD				-30	dBc
$\eta_c$		35			%